



# DK 3 H

## 700772

### Key features

Multipurpose tools that allow to create a natural and smooth roughening effect on all surfaces

Applicable for processing concrete, stone and granite surfaces

Removal of different overlays on concrete as laitance, colors and encrustations

Can be used on vertical surfaces and in restricted areas

The working pressure is done manually by the user

### Technical data

Air consumption	480 l/min, 17.0 cfm
Max. permitted air pressure	7 bar, 100 psi
Vibration value on handle	14.6 m/s <sup>2</sup>
Sound pressure level	≤ 88.7 db(A)
Acoustic power level	≤ 96.7 db(A)
Connection thread	G 3/8"

### Physical parameters

Weight	6.2 kg, 13.7 lbs
Length cm/inch	640 mm / 25"

### Field of application

Quickly removes laitance, projections, encrustation, scale deposits, colour, rust, smoothes roughening and much more.

### Standards

#### EC Machinery Directive 2006/42/EC

The units (DK 1 H - 3 H) had been constructed in accordance with the state of the art and the safety requirements of European Standard **EN ISO 11148-4:2013** (Hand-Held, Non-Electrically Operated Machinery).

## Spare parts

**Pistons with tungsten crown for DK 3 H**

Pistons set  
**700773**



**One set contains:** 3 Pistons with tungsten crown - 1.8 kg / 2.38 lbs