



DTF 35 SH

Electric

Article code	Power	Wattage/HP
800024	3×400 V, 50 HZ	15 kW / 20 HP

Key features	
Cutting width	35 cm / 14"
Distance to wall	10.7 cm / 4"
Cutting depth	Up to 25 mm / 1"
Production / h	Up to 20 m ² / h, 66 f ² / h on full depth

Physical parameters

Weight kg / lbs	307 kg / 677 lbs
Dimensions cm / inch	138×68×113 cm / 54×27×45"

Field of application

Depending on the blade type, hard, brittle to firm or elastic surface materials can be worked e.g.:



- Asphalt and cast asphalt surfaces
- Concrete and cement, synthetic stone, floor tiles
- Screeds of cement, wood cement, ceramic etc.
- Natural stone
- Thermoplastic materials






Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:


- Latex, rubber, soft plastics and foam materials
- Wood, carpets and woven materials

NOTE: The machines are delivered without any blades, drums or sets!

SPARE PARTS

Blades set for shaft 350 mm width					
Article code	Blade count	Spacer count	Space inbetween	Concrete type	
800101	27	80 × 4 mm & 12 × 5 mm	12 mm	Regular	
800102	53	54 × 5 mm & 12 × 5 mm	5 mm	Regular	
800103	98	99 × 2 mm & 12 × 5 mm	2 mm	Regular	
800104	27	80 × 4 mm & 12 × 5 mm	12 mm	Hard	
800105	53	54 × 5 mm & 12 × 5 mm	5 mm	Hard	
800106	98	99 × 2 mm & 12 × 5 mm	2 mm	Hard	

Single parts for shaft				
Article code	Type	Size	Concrete type	
600649	Single blade	230 mm / 9"	Regular	
600648	Single blade	230 mm / 9"	Hard	
600363	Spacer	2 mm		
600258	Spacer	4 mm		
600364	Spacer	5 mm		

Distance sets		
800119	Distance bush shaft set 10 cm	
800120	Distance bush shaft set 15 cm	
800121	Distance bush shaft set 17 cm	
800122	Distance bush shaft set 20 cm	
800123	Distance bush shaft set 25 cm	

NOTE: The sets consists of three bushings: two custom made and one universal.