



MH 34

700741

Key features

Air consumption	125 L/Min., 4.4 cfm
Max. permitted air pressure	7 bar, 100 psi
Vibration value on handle	10.29 m/s ²
Sound pressure level	≤ 98.2 db(A)
Acoustic power level	≤ 106.2 db(A)

Field of application

Ideal for removing carpet and plaster, scabbling natural stone, chiselling out joints and pointing masonry. Available with different chisels.

Physical parameters

Weight	2.8 kg / 6.2 lbs
Connection thread	G 3/8"

Packaging



Case size 475×360×110 mm / 18.7×14.1×4.3"






One box contains

MH 34 chisel hammer
Hose connection G3/8 × 10 mm
Auxiliary handle
Allen key hexagonal
Tube of grease
Operating manual

Recommended lubricants

BP	Energol RD-E46
Mobil	Almo Oil 325
Shell	Torcula 100
DEA	Arkas 32
Texaco	Aries 32
Esso	Arox EP 46 or EP 100

Spare parts

Chisels					
40 × 520 mm 700207	40 × 250 mm 700194	24 × 190 mm 700193	290 mm 700196	60 × 300 mm 708582	24 × 260 mm 700195
					
100 × 180 mm - 700205			Carpet removal chisel, 210 mm - 706867		
					
Pitching tools					
3×3 - 700199	4×4 - 700200	5×5 - 700201	7×7 - 700202		
					
Holder hexagonal - 700204		Holder round - 700198			
					
Spare parts of the unit					
Chisel holder - 700294		Auxiliary handle - 700342			
					