



# VA 35 SH

## Electric

Article code	Power	Wattage / HP
<b>800112</b>	3 × 400 V, 50 HZ	11 Kw / 15HP
<b>800193</b>	3 × 480 V, 60 HZ	12.6 Kw / 17HP

### Key features

Working width	35 cm / 14"
Distance to wall	14 cm / 5.5"
Depth hard concrete	8 mm / .31"
Depth regular concrete	11 mm / .43"
Production / h	60-65 m <sup>2</sup> / 700 sqf
Standard cutters	Octagonal carbide

### Physical parameters

Weight kg / lbs	346 kg / 763 lbs
Dimensions	681x1395x1014 mm / 27×55×40"
Hose connection	102 mm / 4" (76 mm / 3")

### Pairing with

#### T7 dust extractor



#### T8 dust extractor



#### T10 dust extractor (electric, LPG)



### Field of application

**Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:**

- Asphalt and cast asphalt surfaces
- Concrete and cement, synthetic stone, floor tiles
- Screeds of cement, wood cement, ceramic etc.
- Natural stone
- Metals
- Thermoplastic materials

**Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:**

- Latex, rubber, soft plastics and foam materials
- Wood, carpets and woven materials



# Spare parts

Octagonal cutters for VA 35 SH	Octagonal cutters set 800198		Complete drum 600312		<p><b>Application:</b> With tungsten carbide inserts, for roughening concrete and asphalt, for removing old coatings</p> <p><b>One set contains:</b> 4 flail shafts, 124 washers, 80 pcs octagonal cutters large</p>
--------------------------------	------------------------------	---	----------------------	---	--